

### **GSA Sewage Service Specifications**

*[Note: The following specification assumes a single delivery point at the Government Facility for which service is required. If more than one delivery point is desired, this specification should be modified to include requirements for each delivery point.]*

(a) The Contractor shall provide sewage service to *[Enter name and location of specific premises to be served]*. The sewage service provided by the Contractor shall meet the Government's everyday needs for the proper operation of the stated facility. The Contractor shall operate its sewage disposal and treatment facilities in conformity with (1) all applicable laws, rules, codes, industry standards, permits, and regulations, promulgated by any and all governmental authorities having jurisdiction.

Estimated annual service requirements are:

Maximum daily volume \_\_\_\_\_<sup>\*\*</sup> m<sup>3</sup> (\_\_\_\_\_ gal.)  
Total annual volume \_\_\_\_\_<sup>\*\*</sup> m<sup>3</sup> (\_\_\_\_\_ gal.)

*[\*\*Note: If metric units of measure are acceptable to the governing regulatory body, entries should be in metric units. Otherwise, entries should be in regulatory body approved units of measure. A table for conversion of commonly used English units to metric units is attached to this specification.]*

*[If changes in annual requirements during the contract term are foreseeable, the above description of annual usage should be modified to indicate the expected changes.]*

The amounts shown in this paragraph are estimates only and do not constitute a Government usage guarantee. The sewage services to be delivered by the Contractor are [ ]metered [ ]nonmetered. All meters (if any) shall be installed by the Contractor in a manner that allows verification of billing determinants by Government personnel. If nonmetered, the total sewage outflow shall be estimated as \_\_\_\_\_ percent of the Government facility's actual monthly metered water consumption. The Government's delivery of sewage to the Contractor shall be by [ ]gravity main [ ]force main. The sewage to be delivered [ ]shall not be pretreated by the Government [ ]shall be pretreated by the Government in the following manner: \_\_\_\_\_  
\_\_\_\_\_.

*[Include the following information on concentrations of BOD and TSS only if required by potential suppliers.]*

Expected monthly average concentration for Biological Oxygen Demand (BOD) and Total Suspended Solids (TSS) in the sewage are \_\_\_\_\_<sup>\*\*</sup> mg/l and \_\_\_\_\_<sup>\*\*</sup> mg/l, respectively.

(b) The point of service connection between the Government facility and the Contractor's system shall be as shown in Attachment A of Section J (map or diagram to be included by the ordering agency).

(c) *[Consider use of the following for new connection.]*

The [ ]inside [ ]outside diameter of the Government's pipeline at the point of entry is \_\_\_\_\_<sup>\*\*</sup> mm (\_\_\_\_\_ in.) The Contractor shall design, construct, own, operate, and maintain the facilities necessary to connect the Government facility to its existing system and to meet the Government's full sewage service requirements during the term of this contract. The Contractor shall provide in Attachment A of Section J a schematic diagram of Contractor connecting facilities to be installed on Government premises, if any.